## SINGLE POINT STIRRING DRIVES WITH EXTERNAL CONTROL UNIT

Designed for chemical, biotechnical and medical applications of all kinds, developed for maximum requirements, maximum mechanical, thermal and chemical stability as well as uncompromising continuous operation.



## MIXdrive 1

Ultra flat, wear-free magnetic stirrer with 1 stirring position, suitable for vessels up to 10,000 ml.



№ Submersible, up to +95 °C

₹ Extremely robust construction

₹ Integrable in systems

Developed and made in Germany







| Туре                               | MIXdrive 1  |
|------------------------------------|---|
| Stirring points                    | 1   |
| Stirring volume/stirring point     | 1 - 10,000 ml                                     |
| Stirring power (max.)              | 20 W  |
| Material housing                   | Stainless steel                                   |
| Perm. operation conditions (Basic) | -10 °C up to +50 °C in air, up to +50 °C in water |
| Perm. operation conditions (HT)    | up to +200 °C in air, up to +95 °C in water       |
| Operating voltage (max.)           | 48 VDC  |
| Dimensions (WxDxH)                 | 180 x 180 x 38 mm                                 |
| Protection category                | IP68  |
| Weight (gross)                     | approx. 3.3 kg                                    |
| Order no. Basic-version            | 40001   |
| Order no. HT-version               | 40201   |

Individual units and dimensions on request.

3 years warranty on material and manufacturing.

We reserve the right to make technical alterations. We do not assume liability for errors in printing or typeing.

1 stirring position, 100% maintenance-free and wear-free by inductive 2mag-Magnetic-Drive concept for powerful mixing of solutions, jerk-free stirring even at low speeds.

Fully encapsulated and hermetically sealed stainless steel housing, IP68, water-, dust-, and germproof, extremely robust construction and performance, easy to clean and maximum resistance, submersible in water- or oil baths, suitable for the use in CO<sub>2</sub>-incubators and ovens.

Two different temperature areas available: **Basic-version** up to +50 °C, **HT-version** up to +95 °C submerged in water baths and up to +200 °C in ovens, individual dimensions on request.

Please order control unit separately!

## Compatible control units

MIXcontrol eco
MIXcontrol eco DINrail
MIXcontrol 20
MIXcontrol 40 (only in combination with distriBOX 4)

## Accessories

ASTEROID 40 - Stirring bar Stirring bar remover PTFE Extension cord for MIXdrive distribOX 4 - distributor

10 www.2mag.de