

CONTROL UNITS FOR MIXdrive STIRRING DRIVES

Designed for 2mag MIXdrive stirring drives. For chemical, biotechnical and medical applications of all kinds.

MIXcontrol eco

Price-optimized control unit for small medium volumes and the connection of 1 stirring drive MIXdrive.

- Price-optimized
- 120 up to 1,200 rpm
- SoftStart

magnetic motion



Type	MIXcontrol eco
Speed range	120 - 1,200 rpm
Stirring power (max.)	10 W
Power setting	-
Material housing	Plastic
Perm. operation conditions	0 °C up to +40 °C (at 80% humidity)
Electrical data	100-240 V / 50-60 Hz / 0.75 A
Dimensions (WxDxH)	65 x 50 x 45 mm
Protection category	IP20
Weight (gross)	approx. 0.5 kg
Order no.	90100

Individual units and dimensions on request.
3 years warranty on material and manufacturing.
We reserve the right to make technical alterations. We do not assume liability for errors in printing or typing.

Control unit with 10 watts stirring power, speed range from 100 up to 1,200 rpm, SoftStart for reliable catching/centering and safe accelerating of the stirring bar.

Compatible stirring drives

- MIXdrive 1
- MIXdrive 1 eco
- MIXdrive 1 XS
- cuvetteMIXdrive 1
- MIXdrive 6
- MIXdrive 15
- MIXdrive 60