

CONTROL UNITS FOR MIXdrive STIRRING DRIVES

Designed for 2mag MIXdrive stirring drives. For chemical, biotechnical and medical applications of all kinds.

MIXcontrol eco DINrail

Price-optimized control unit for DIN installation (electrical cabinets).

- 🌀 DINrail installation (electrical cabinets)
- 🌀 120 up to 1,200 rpm
- 🌀 SoftStart

magnetic motion



Type	MIXcontrol eco DINrail
Speed range	120 - 1,200 rpm
Stirring power (max.)	10 W
Power setting	-
Material housing	Plastic
Perm. operation conditions	0 °C up to +40 °C (at 80% humidity)
Operating voltage (max.)	24 VDC
Dimensions (WxDxH)	24 x 100 x 120 mm
Protection category	IP20
Weight (gross)	approx. 0.5 kg
Order no. 0-10 V	90150
Order no. with potentiometer	90140

Individual units and dimensions on request.
3 years warranty on material and manufacturing.
We reserve the right to make technical alterations. We do not assume liability for errors in printing or typing.

Control unit for DINrail installation (electrical cabinets) for small to medium volumes and the connection of one stirring drive MIXdrive, with analog interface 0-10 volts or potentiometer for ON/OFF and speed adjustment.

Also available with RS232 interface.

Control unit with 10 watts stirring power, speed range from 100 to 1,200 rpm, SoftStart for reliable catching/centering and safe accelerating of the stirring bar.

Compatible stirring drives

- MIXdrive 1
- MIXdrive 1 eco
- MIXdrive 1 XS
- cuvetteMIXdrive 1
- MIXdrive 6
- MIXdrive 15
- MIXdrive 60

