

CONTROL UNITS FOR MIXDRIVE MTP STIRRING DRIVES

Designed for MIXdrive MTP stirring drives.

MIXcontrol MTP

Powerful control unit for connection of one stirring drive MIXdrive 6/12/24/96 MTP.

- Speed range 100 - 2.000 rpm
- For stirring drives MIXdrive MTP
- Extremely robust construction
- Developed und Made in Germany

magnetic motion



Type	MIXcontrol MTP
Speed range	100 - 2.000 rpm
Stirring power (max.)	10 W
Power setting	4-step (25/50/75/100%)
Material housing	Stainless steel
Permitted operation conditions	0 °C up to +40 °C (at 80% humidity)
Electrical data	100-240 V / 50-60 Hz / 1,5 A
Dimensions (WxDxH)	200 x 155 x 38 mm
Protection category	IP20
Weight (gross)	approx. 1.4 kg
Order no. MIXcontrol MTP	90250
Order no. MIXcontrol MTP RS232	90252

Individualisierte Ausführungen und abweichende Gerätegrößen auf Anfrage.
3 Jahre Gewährleistung auf Material- und Fabrikationsfehler.
Technische Änderungen vorbehalten. Für Druck- und Schreibfehler keine Haftung.

Universal control unit for the connection of one stirring drive MIXdrive MTP, universal 10 watts stirring power, wide speed range from 100 up to 2,000 rpm, jerk-free stirring also at low speeds, 4-step power setting (25/50/75/100%).

Clear digital display for speed- and power settings, SoftStart for reliable catching/centering and safe accelerating of the stirring bar.

QuickSet for quick setting of start- and maximum speed, automatic memory function to save the last settings, resistant stainless steel housing, easy to clean.

Also available with RS232 interface.

Interfaces (0-10 volts, 4-20 mA, USB, Ethernet) and customized software adaption on request.

Compatible stirring drives

- MIXdrive 6 MTP
- MIXdrive 12 MTP
- MIXdrive 24 MTP
- MIXdrive 96 MTP

