## CONTROL UNITS FOR MIXdrive STIRRING DRIVES

Designed for 2mag MIXdrive stirring drives. For chemical, biotechnical and medical applications of all kinds.



## MIXcontrol 40

Powerful control unit, for 2mag MIXdrive series, developed for the hard daily lab use and uncompromising continuous operation.

- ₱ For connection of 2 stirring drives MIXdrive
- → Developed and made in Germany







Туре	MIXcontrol 40
Speed range	100 - 2,000 rpm
Stirring power (max.)	40 W
Power setting	4 - 40 W (10-step)
Material housing	Stainless steel
Permitted operation conditions	0 °C up to +40 °C (at 80% humidity)
Electrical data	100-240 V / 50-60 Hz / 1.5 A
Dimensions (WxDxH)	200 x 155 x 38 mm
Protection category	IP20
Weight (gross)	approx. 1.4 kg
Order no.	90400
Order no. RS232	90410

Individual units and dimensions on request.

3 years warranty on material and manufacturing.

We reserve the right to make technical alterations. We do not assume liability for errors in printing or typeing.

Powerful control unit for the connection of up to two stirring drives MIXdrive, powerful 40 watts stirring power, wide speed range from 100 up to 2,000 rpm, jerk-free stirring also at low speeds, power setting (10-steps) for high power with regard to large and viscous stirring amounts and reduced power for the warming-free continuous operation of MIXdrive stirring drives.

Clear digital display for speed- and power settings, SoftStart for reliable catching/centering and safe accelerating of the stirring bar. QuickSet for quick setting of start- and maximum speed, automatic memory function to save the last settings, resistant stainless steel housing, easy to clean.

Also available with RS232 interface.

Interfaces (0-10 volts, 4-20 mA, USB, Ethernet) and customized software adaption on request.

## Compatible stirring drives

MIXdrive 1 (only in combination with distriBOX 4)

MIXdrive 1 eco (only in combination with distriBOX 4/8)

MIXdrive 6

MIXdrive 15

MIXdrive 60

23 www.2mag.de