

Premium Double Layer Shaking Incubators



ZWYR-2112B



ZWYR-2102C



ZWYR-2102

Description:

These new double layer shaking incubators in a class of their own, are specially developed a cost effective and space saving solution for the modern biological engineering departments; the units are widely used in the applications of germ culture, hybridization, biochemical research, enzyme and cellular tissues. These incubators have a smooth compact design, which are very efficient and have an excellent floor space/performance factor. The double layer shaking frame supports two trays above each other, doubles the capacity for smaller flasks, while after removing the top tray (Shaking frame upgrade is required).

Features:

- 4.3"/5.6" LCD touch screen panel clearly indicates all parameters in one page display and makes it easy to change the operating parameters settings, even those multi set points under programmable mode intuitively.
- P.I.D microprocessor controller provides unmatched versatility by enable users to create personalized program (with up to 9 segments, with cycling) to automate changes to function parameters.
- Large double fold tempered glass window on the front doors together with the fluorescent light provide complete visibility of chamber interior.
- Mirror-finished high quality #304 stainless steel for excellent durability of interiors.
- Non-volatile memory for set point retention after power interruption.
- Robust triple eccentric counterbalanced drive in cast iron housing provides vibration and trouble free operation with high shaking speed up to 300rpm even when both layers are fully loaded.
- Quality brushless AC inductive motor supports reliable, quiet and smooth shaking movements up to top speed even when fully loaded with 90 pieces of 250ml flasks (ZWYR-2112B, ZWFR-2112).
- Auto-defrosting system, ensuring long-terms non-frosting operation with low temperature setpoints.
- Non-volatile memory saves settings during a power outage and automatically restarts the unit after power is restored.
- Audible and visual alarms on over temperature and motor overheating, and automatically cut off the power.
- Soft start and smooth acceleration when doors are closed after short opens.
- Dedicated single layer shaking frame is available for the ease of using large flasks.
- For data recording, the units are equipped with a built-in thermo printer as standard, so that operators could check how the performance parameters vary according to specified process without having to be on site.
- Timer up to 9999 mins under fixed value control mode.
- **New** UV light reduces the air burden, keeping the chamber contamination free.
- Predrilled standard tray included, without clamps.



Double Layer Shaking Frame



Flask (ml)	50ml	100ml	250ml	500ml	750ml	1000ml	2000ml	3000ml	5000ml	P8010	P8012
ZWYR-2102C	56	56	28	22	18	6*	3*	2*	2*	4	9
ZWYR-2102	104	104	56	44	30	24	7*	6*	4*	8	19
ZWYR-2112B	164	164	90	74	52	36	13*	8*	6*	12	30
ZWFR-2112	164	164	90	76	48	44	12*	8*	6*	12	30

* Applies only when single layer shaking frame is equipped.

Specifications:

Model	ZWYR-2102C	ZWYR-2102	ZWYR-2112B	ZWFR-2112
Control	P.I.D Microprocessor			
Control Mode	Fix Value or Program (up to 9 Segments)			
Control Panel	LCD Touch Screen			
Volume (L)	170	330	580	580
Working Temperature(°C)	5-25			
Shaking Speed (rpm)	30-300			30-240
Stroke (mm)	26		35	1 to 50 Stepless
Shaking Mode	Orbital			Reciprocal
Temperature (°C)	4 to 60			
Temperature Accuracy	±0.1°C			
Temperature Uniformity	±1°C@37°C			
Timer	1 to 9999 mins			
Tray (mm) (WxD)	496x350	734x458	970x560	940x580
Inner dimensions (mm) (WxDxH)	615x450x640	845x530x765	1105x850x664	1105x850x664
Exterior dimensions (mm) (WxDxH)	720x685x1310	950x755x1445	1430x880x1700	1430x880x1700
Packing dimensions (mm) (WxDxH)	800x770x1490	1030x870x1640	1500x950x1860	1500x950x1860
Net/Gross Weight (kg)	195/238	255/320	460/570	486/596
Power (W)	1000	1050	1600	1600
Electricity	220-240V 50/60 Hz			
Approval	CE, ISO			
Security	Over-temperature Protection, Compressor Overload Protection, Electrical			
Additional	Built-in Printer, RS485 Interface Kit (Option)			

Ordering Information:

Part NO.	Description	Part NO.	Description
ZWYR-2102C	ZWYR-2102C, 170L, Premium Double Layer Shaking Incubator 4-60, 30-300rpm	P8001	T Clamp, S/S, for 50ml Flask, with Spring Retainer
ZWYR-2102	ZWYR-2102, 330L, Premium Double Layer Shaking Incubator 4-60, 30-300rpm	P8002	T Clamp, S/S, for 100ml Flask, with Spring Retainer
ZWYR-2112B	ZWYR-2112B, 580L, Premium Double Layer Shaking Incubator 4-60, 30-300rpm	P8013	T Clamp, S/S, for 150ml Flask, with Spring Retainer
ZWFR-2112	ZWFR-2112, 580L, Premium Reciprocal Double Layer Shaking Incubator 4-60, 30-240rpm	P8003	T Clamp, S/S, for 250ml Flask, with Spring Retainer
P5001	Single Layer Shaking Frame for ZWY-1102C/2102C, ZWYR-2102C, Stl S/C#	P8014	T Clamp, S/S, for 300ml Flask, with Spring Retainer
P5002	Single Layer Shaking Frame for ZWY-1102/2102, ZWYR-2102C, Stl S/C	P8004	T Clamp, S/S, for 500ml Flask, with Spring Retainer
P5003	Single Layer Shaking Frame for ZWY-1112B/2112B, ZWYR-2112B, Stl S/C	P8005	T Clamp, S/S, for 750ml Flask, with Spring Retainer
P5016	RS-485 Interface	P8006	T Clamp, S/S, for 1000ml Flask, with Spring Retainer
P6010	Tray for ZWY-1102C/2102C/ZWYR-2102C, S/S※	P8007	T Clamp, Spring S/S, for 2000ml Flask, with Spring Retainer
P6011	Tray for ZWY-1102/2102/ZWYR-2102, S/S	P8008	T Clamp, Spring S/S, for 3000ml Flask, with Spring Retainer
P6012	Tray for ZWY-1112B/2112B/ZWYR-2112B, S/S	P8009	T Clamp, Spring S/S, for 5000ml Flask, with Spring Retainer
P6013	Tray for ZWF-1112/2112/ZWFR-2112, S/S	P8010	Tube Rack S/S
P7011	Universal Tray for ZWY-1102C/2102C/ZWYR-2102C	P8011	Tube Rack ABS Plastic
P7012	Universal Tray for ZWY-1102/2102/ZWYR-2102, Ful Pcs	P8012	Clamp for 96 Well Plate, S/S
P7013	Universal Tray for ZWY-1112B/2112B/ZWYR-2112B, Ful Pcs	P8017	Sticky Mat, 20 x 20cm
P7014	Universal Tray for ZWF-1112/2112/ZWFR-2112, Ful Pcs	# Stl S/C: Spray Coated Steel, ※ S/S: Stainless Steel	

Labwit quality assurance program demands the continuous assessment and improvement of all Labwit products. Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact Labwit or their representatives if you require more details